



A TURN AHEAD OF THE COMPETITION

Garrett G Series Turbochargers: G25-550 G25-660



G series turbochargers feature the latest innovations in turbocharger technology. Advanced compressor and turbine aero offer enthusiasts a wide range of performance boosting solutions for 1.4L - 3.0L engine platforms. Standard and reverse rotation options are offered with a variety of turbine housing configurations making it easy to select the right turbocharger for your application.



Scan Here

Garrett
ADVANCING MOTION

A TURN AHEAD OF THE COMPETITION

Garrett G Series G25-550 | G25-660



Features:

- G SERIES COMPRESSOR AERODYNAMICS FOR MAXIMUM HP
- G SERIES TURBINE WHEEL AERO WITH IMPROVED EFFICIENCY
- STANDARD AND REVERSE ROTATION CONFIGURATIONS
- MAR-M ALLOY TURBINE WHEEL RATED UP TO 1050°C
- STAINLESS STEEL TURBINE HOUSINGS RATED UP TO 1050°C
- FULLY MACHINED SPEED SENSOR AND PRESSURE PORTS
- OIL RESTRICTOR AND WATER FITTINGS INCLUDED

	Compressor					Turbine	
G25-550 Standard Rotation	HP: 300-550	Inducer	Exducer	Trim	A/R	Inducer	Exducer
	Disp: 1.4L - 3.0L	48mm	60mm	65	0.70	54mm	49mm
Non Wastegated Assembly Kit Includes Super Core and Turbine Kit	Assembly Kit PN		A/R	Inlet	Outlet	Wastegate	Divided
	871389-5004S		0.72	V-Band	V-Band	Free Float	N
	871389-5005S		0.92	V-Band	V-Band	Free Float	N
Wastegated Turbo PN assembled and calibrated by Garrett® to 1.0 bar (14.7PSI)	Turbo PN		A/R	Inlet	Outlet	Wastegate	Divided
	877895-5001S		0.49	T25	V-Band	Yes	N
	877895-5003S		0.72	V-Band	V-Band	Yes	N
	877895-5004S		0.92	V-Band	V-Band	Yes	N
	877895-5011S		0.92	T4	V-Band	Yes	Y
G25-550 Reverse Rotation	HP: 300-550	Inducer	Exducer	Trim	A/R	Inducer	Exducer
	Disp: 1.4L - 3.0L	48mm	60mm	65	0.70	54mm	49mm
Non Wastegated Assembly Kit Includes Super Core and Turbine Kit	Assembly Kit PN		A/R	Inlet	Outlet	Wastegate	Divided
	871390-5004S		0.72	V-Band	V-Band	Free Float	N
	871390-5005S		0.92	V-Band	V-Band	Free Float	N
Wastegated Turbo PN assembled and calibrated by Garrett® to 1.0 bar (14.7PSI)	Turbo PN		A/R	Inlet	Outlet	Wastegate	Divided
	877895-5007S		0.72	V-Band	V-Band	Yes	N
	877895-5008S		0.92	V-Band	V-Band	Yes	N
	877895-5013S		0.92	T4	V-Band	Yes	Y
G25-660 Standard Rotation	HP: 350-660	Inducer	Exducer	Trim	A/R	Inducer	Exducer
	Disp: 1.4L - 3.0L	54mm	67mm	65	0.70	54mm	49mm
Non Wastegated Assembly Kit Includes Super Core and Turbine Kit	Assembly Kit PN		A/R	Inlet	Outlet	Wastegate	Divided
	871389-5010S		0.72	V-Band	V-Band	Free Float	N
	871389-5011S		0.92	V-Band	V-Band	Free Float	N
Wastegated Turbo PN assembled and calibrated by Garrett® to 1.0 bar (14.7PSI)	Turbo PN		A/R	Inlet	Outlet	Wastegate	Divided
	877895-5002S		0.49	T25	V-Band	Yes	N
	877895-5005S		0.72	V-Band	V-Band	Yes	N
	877895-5006S		0.92	V-Band	V-Band	Yes	N
	877895-5012S		0.92	T4	V-Band	Yes	Y
G25-660 Reverse Rotation	HP: 350-660	Inducer	Exducer	Trim	A/R	Inducer	Exducer
	Disp: 1.4L - 3.0L	54mm	67mm	65	0.70	54mm	49mm
Non Wastegated Assembly Kit Includes Super Core and Turbine Kit	Assembly Kit PN		A/R	Inlet	Outlet	Wastegate	Divided
	871390-5010S		0.72	V-Band	V-Band	Free Float	N
	871390-5011S		0.92	V-Band	V-Band	Free Float	N
Wastegated Turbo PN assembled and calibrated by Garrett® to 1.0 bar (14.7PSI)	Turbo PN		A/R	Inlet	Outlet	Wastegate	Divided
	877895-5009S		0.72	V-Band	V-Band	Yes	N
	877895-5010S		0.92	V-Band	V-Band	Yes	N
	877895-5014S		0.92	T4	V-Band	Yes	Y